



Versatility and Durability

Safe-Way's option in an expanded polystyrene insulated door with steel skins inside and out provides durability and versatility with multiple color and window options typically not available in commercial applications. Whether you need doors for an industrial warehouse facility or for a pole barn, this product fits the bill.

Make a Statement.



Commercial

Polystyrene Insulated Sandwich Door Model 270

Insulated Windows



8" x 24"



12" x 24"



16" x 34"


Product Features & Specifications

- Standard sizes up to 20' 2" wide
- 2" expanded polystyrene insulation provides an R-Value of 10.25
- Continuous vertical backer plates at each hinge attachment point
- Doors are finished with a three coat process in white, brown, almond, sandtone, hunter green, desert tan and bronze.
- Interior and exterior skin are 27 gauge, woodgrain embossed with minor ribs running horizontally on the exterior skin of each section.
- Hardware is manufactured out of hot dipped galvanized steel. Hinges are 14 gauge and rollers are 10 ball bearing steel.
- Track is available in 2" or 3". Vertical lift, high lift, follow the roof slope, and low headroom options are available. Consult your dealer for details.
- Doors are balanced by a torsion spring counterbalance system constructed of oil tempered torsion springs. High cycle spring options of 25,000, 50,000, or 100,000 are available.
- Doors come standard with an inside side lock. A keyed lock-bar locking system is available.


Section Colors



Construction



- A. Finish Painted Coat
- B. Primer Coat
- C. Galvanized Layer
- D. Steel



- A. 10 ball steel rollers provide long lasting durability
- B. Heavy duty galvanized 14 gauge hardware
- C. Tongue and groove design provides weathertight section joints
- D. 2" expanded polystyrene insulation provides an R-Value of 10.25.
- E. Steel skins inside and out provide maximum durability.
- F. Aluminum bottom retainer with vinyl weatherstrip.

Distributed by:



As Safe-Way Door constantly strives to improve our product, all specifications listed in this informative brochure are subject to change without notice or obligation. Printed color may vary from actual color, please check with your local dealer for color swatches.
8-15

3814 East U.S. 30 • Warsaw, IN 46580
574-267-4861 • Fax: 574-267-2871
safewaydoor.com